

产品承认书

PRODUCT SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER NAME	
客户料号 P/N OF CUSTOMER	
承认字号 APPROVAL NO.	
产品名称 PRODUCT NAME	贴片型负温度系数热敏电阻 CHIP TYPE NTC THERMISTOR
规格型号 TYPE SPECIFICATION	SNC104B ₂ 3435F0402E
承认书版本号 APPROVAL SHEET VERSION	1.0
承认日期 DATE OF APPROVAL	

供 应 商 SUPPLIER		
制定 DESIGNED	审核 CHECKED	批准 APPROVED
供应商品管部印鉴 SUPPLIER QA SEAL		

客 户 CUSTOMER		
检验 INSPECTED	审核 CHECKED	批准 APPROVED
客户承认印鉴 CUSTOMER APPROVAL SEAL		



修订履历

[illegible]

目 录

CONTENTS

1、规格型号 PART IDENTIFICATION	1
2、产品特性 PRODUCTION FEATURES	2
2.1 技术参数 TECHNICAL PARAMETER	2
2.2 外形尺寸、材质 PRODUCTION DIMENSION、MATERIAL	2
3、检验规则 INSPECTION REGULATIONS	3
3.1 出厂检验 DELIVERY INSPECTION	3
3.2 型式检验 PATTERN INSPECTION	5
4、包装、贮存 PACKAGE & STORAGE	7
4.1 包装 PACKAGE	7
4.2 贮存 STORAGE	7

1、规格型号 PART IDENTIFICATION

SN C 104 B₂ 3435 F 0402 E
 ① ② ③ ④ ④ ⑥ ⑦ ⑧


① 产品类别 PART NUMBER ENTIFICATION	SN指敏感型负温度系数热敏电阻;
	SN INDICATES SMD NTC THERMISTOR
② 系列类别 SERIES CATEGORY	C指贴片
	C REFERS TO THE PATCH
③ 产品阻值 (25°C零功率电阻值) PRODUCT RESISTANCE (25°C ZERO POWER RESISTANCE)	104指100KΩ
	104 MEANS 100 KΩ
④ B 值代码 B-VALUE CODE	B2指 25/85
	B2 MEANS 25/85
⑤ B 值数值 B-VALUE TOLERANCE	3435指B值为3435K
	3435 MEANS THAT B VALUE IS 3435K
⑥ 阻值误差 PACKAGING STYLE	F指±1%
	F MEANS ±1%
⑦ 本体尺寸 BODY SIZE	0402指2.2图所示尺寸
	0402 REFERS TO THE SIZE SHOWN IN FIGURE 2.2
⑧ 环保产品 ENVIRONMENTAL PROTECTION PRODUCTS	E表示环保产品。
	E STANDS FOR ENVIRONMENTALLY FRIENDLY PRODUCTS.

2、产品特性 PRODUCTION FEATURES

2.1 技术参数 TECHNICAL PARAMETER

型号规格 SPECIFICATION AND MODEL	额定零功率电阻值 RATED ZERO POWER RESISTANCE VALUE	B (K)	耗散系数 DISSIPATION COEFFICIENT (S)	热时间常数 THERMAL TIME CONSTANT (S)	额定功率 RATED POWER (mw)	工作温度范围 (°C)
SNC104B ₂ 3435F0402E	100K	3435	≥ 1	≤ 3	100	-40~125

2.2 外形尺寸 PRODUCTION DIMENSION



(单位UNIT: MM)



3、检验规则 INSPECTION REGULATIONS

3.1 出厂检验 DELIVERY INSPECTION

序号 SEQUENCE	检测项目 TEST ITEM	检验方法 INSPECTION METHOD	性能要求 PERFORMANCE REQUIREMENT
(1)	R ₂₅	将待测品置于 25°C 高精度油槽内稳定后 测量 THE PRODUCT TO BE MEASURED IS PLACED IN A 25°C HIGH PRECISION OIL TANK FOR STABILITY	100KΩ±1%
(2)	B _{25/50}	将待测品置于 25°C、85°C 精度油槽内稳 定后测量 THE PRODUCT TO BE TESTED IS PLACED IN A 25°C, 85°C PRECISION OIL TANK AND THEN MEASURED	3435K±1%
(3)	外观 APPEARANCE	在 20X 的显微镜下目测检查 VISUAL INSPECTION UNDER A 20X MICROSCOPE	产品符合 2.2 的外形要求，无腐蚀、 流挂、断片、崩边崩角等 THE PRODUCTS MEET THE REQUIREMENTS OF 2.2 SHAPE, NO CORROSION, FLOW HANGING, FRAGMENTATION, EDGE BREAKAGE, ETC
(4)	尺寸 DIMENSION	用精度不小于 0.01mm 的游标卡尺测量 MEASURE WITH VERNIER CALIPER WITH ACCURACY NOT LESS THAN 0.01MM	符合 2.2 的外形尺寸 CONFORM TO THE DIMENSIONS OF 2.2
(5)	可焊性 WELDABILITY	焊接温度 WELDING TEMPERATURE: 245± 5°C; 浸入时间 IMMERSION TIME: 3±1s	着锡面积 TIN AREA ≥ 95%

(6)	耐焊性 WELDING RESISTANCE	焊接温度 WELDING TEMPERATURE: $260 \pm 10^{\circ}\text{C}$ 浸入时间 IMMERSION TIME: $10 \pm 1\text{s}$	无外观损伤, 着锡面积 $\geq 75\%$ NO APPEARANCE DAMAGE, TIN AREA $\geq 75\%$ $ \Delta R_{25}/R_{25} \leq 5\%$
-----	------------------------------	---	---

3.2 型式检验 PATTERN INSPECTION

序号 SEQUENCE	检验项目 ITEMS	检验标准 STANDARD	检验标准 STANDARD	性能要求 PERFORMANCE REQUIREMENTS
(1)	端头强度 END STRENGTH	IEC68-2-21	 F: 0402 $\geq 3N$	无外观损伤 NO COSMETIC DAMAGE
(2)	抗弯强度 BENDING STRENGTH	IEC68-2-21	 h: $1 \pm 0.1mm$	无外观损伤 NO COSMETIC DAMAGE $\Delta R_{25} / R_{25}$ $\leq 3\%$
(3)	跌落 FALL	IEC68-2-32	跌落高度 DROP HEIGHT: $1.0 \pm 0.1m$ 跌落次数 NUMBER OF DROPS: 1 跌落面 DROP SURFACE: 水泥 CEMENT	无外观损伤 NO COSMETIC DAMAGE $\Delta R_{25} / R_{25}$ $\leq 1\%$ $\Delta B / B$ $\leq 2\%$
(4)	湿热负载 DAMP-HEAT LOAD	IEC68-2-2/IEC68-2-3/CNS5550	温度 TEMPERATURE: $40 \pm 2^\circ C$ 湿度 HUMIDNESS: 90~95%RH 时间 TIME: $500 \pm 12h$; 工作电流 WORKING CURRENT	无外观损伤 NO COSMETIC DAMAGE $\Delta R_{25} / R_{25}$ $\leq 5\%$ $\Delta B / B$ $\leq 2\%$
(5)	高温存储 HIGH TEMPERATURE STORAGE	IEC68-2-2/CNS5550	温度 TEMPERATURE: $125 \pm 2^\circ C$ 时间 TIME: $1000 \pm 24h$	无外观损伤 NO COSMETIC DAMAGE $\Delta R_{25} / R_{25}$ $\leq 5\%$ $\Delta B / B$ $\leq 2\%$
(6)	冷热冲击 THERMAL SHOCK	IEC68-2-14	温度 TEMPERATURE: $-40 \pm 125^\circ C$; 周期 PERIOD: 100,30min/cyc	无外观损伤 NO COSMETIC DAMAGE $\Delta R_{25} / R_{25}$ $\leq 5\%$ $\Delta B / B$ $\leq 2\%$
(7)	低温存储 LOW TEMPERATURE	IEC68-2-1	温度 TEMPERATURE: $-40 \pm 2^\circ C$ 时间 TIME: $1000 \pm 24h$	无外观损伤 NO COSMETIC DAMAGE

	STORAGE			$ \Delta R_{25}/R_{25} \leq 2\%$ $ \Delta B/B \leq 2\%$
(8)	耐久性 DURABILITY	UL1434	环境温度 ENVIRONMENT TEMPERATURE: $25 \pm 2^\circ\text{C}$ 工作电流 WORKING CURRENT 周期 PERIOD: 6000	无外观损伤 NO COSMETIC DAMAGE $ \Delta R_{25}/R_{25} \leq 5\%$ $ \Delta B/B \leq 2\%$

4、包装、贮存 PACKAGE & STORAGE

4.1 包装 PACKAGE

序号 SEQUENCE	包装方式 PACKAGING	包装材料、尺寸 PACKAGING MATERIAL & DIMENSION	产品数量 QUANTITY OF PRODUCT
(1)	编带 BRAID	0402纸带, 标准带轮 0402 PAPER TAPE, STANDARD PULLEY	10000PCS
(2)	内包装盒 INNER BOX	纸箱CARTON, L×W×H=185mm×70mm×190mm	
(3)	外包装箱 OUTER PACKING BOX	纸箱CARTON, L×W×H=370mm×205mm×215mm	

4.2 贮存 STORAGE

产品密封保存, 存放产品的产库环境温度-10℃~+40℃、相对湿度不大于70%, 仓库内不允许有各种有害气体、易爆的产品及腐蚀性的化学物品, 并且无强烈的机械振动、冲击和强辐射的作用, 包装箱应垫高地面至少20cm, 距离墙壁、热源、冷源、窗口或空气入口至少50cm。

- THIS PRODUCT MUST BE KEPT SEALED.
- STORE IN AN ORDINARY ENVIRONMENT (NORMAL ROOM TEMPERATURE, HUMIDITY AND ATMOSPHERIC PRESSURE).
- STORAGE TEMPERATURE: -10℃~+40℃
- RELATIVE HUMIDITY: ≤70%RH.
- KEEP AWAY FROM CORROSIVE GASES, DEOXIDIZING GAS, FLAMMABLE GAS OR DIRECT SUNLIGHT.
- AVOID STRONG MECHANICAL VIBRATION, SHOCK.
- THE PACKING BOX SHOULD BE RAISED AT LEAST 20CM ABOVE THE GROUND AND AT LEAST 50CM AWAY FROM THE WALL, HEAT SOURCE, COLD SOURCE, WINDOWS OR AIR INLET.
- ABNORMAL STORAGE AND OPERATING CONDITIONS MAY CAUSE MALFUNCTION FUNCTION OR FAILURE OF OUR PRODUCTS.